



PROFESSIONAL SERIES SULFUR FILTERS

- **No Chemicals.**
A chemical regenerant is not required.
- **No In-Line Venturi to Plug or Adjust.**
- **No Air Compressor.**
The noise and expense of compressors are eliminated.
- **No Air Release Valve Required.**
- **Small Footprint.**
Small footprint allows for ease of installation.
- **Rugged Mechanical Piston Valve.**
No solenoids or flapper valves to stick.
- **Full Flow Bypass Valve.**
Simple to use valve allows you to bypass the unit for lawn sprinkling or during filter maintenance.
- **Light Weight.**
Catalytic filter media weight 66 lb/cu. ft.

- *Reduces Sulfur*
- *Reduces Iron*
- *Reduces Manganese*
- *Filtration down to 3 microns*

Model Number	Media cu. ft.	Backwash Rate Required @ 40 psi	*Flow Rate (gpm)		Overall Dimensions			Pipe Size
			Service	Peak	L	W	H	
1P1054SULFURPRO	1.0	5 GPM	3	5	12"	15"	64"	1"
1P1248SULFURPRO	1.5	7 GPM	4	6	12"	15"	58"	
1P1354SULFURPRO	2.0	7 GPM	5	8	13"	15"	64"	
1P1665SULFURPRO	3.0	10 GPM	8	11	16"	16"	75"	

NOTE: Residential Sulfur Filter Systems are not designed for continuous flow applications.
(Example: Ground water heat pumps, lawn irrigation, etc.) Specifications subject to change without notice.
*Flow rates listed are dependant upon contaminant level. Higher contaminant levels may require greater contact time.

6610 Guion Road P.O. Box 681430 | Indianapolis, IN 46268
PH: (317) 290-2500 | Toll Free: (800) 873-1103 | Fax (317) 290-2512

www.watcowaterconditioning.com